



furn

SPECIFICATIONS

SHELDON SPECIALTY & TECHNICAL

Fumehoods
HD Shelving
Safety
Sink & Fixtures
Workstations



(MODEL: G-5020)



(MODEL: G-1825)



(MODEL: G-1822)



(MODEL: G-1814)



PRODUCT DESCRIPTION

Eye Wash Units



DECK-MOUNTED DRENCH HOSE (MODEL: G-5020)

Deck mounted, hand-held drench hose with 1/2" IPS U.S. made chrome plated brass squeeze valve with renewable stainless steel seat (optional locking clip, "LC"), insulator handle, stainless steel handle with plastic cover, nylon deck flange, and 8 ft. PVC hose. Unit includes polypropylene 'FS Plus' spray head with integral "flip-top" dust cover, filter and 3.2-GPM flow control orifice. Unit has a ANSI compliant sign.

PEDESTAL-MOUNTED EYE WASH (MODEL: G-1825)

Pedestal mounted eye wash with stainless steel bowl, Schedule 40 galvanized pipe and fittings, 1/2" U.S. made chrome plated stay open ball valve, powder coated cast aluminum flag handle and floor flange. Unit includes (2) polypropylene 'GS Plus' spray heads with integral "flip-top" dust covers, filters and 1.8-GPM flow control orifices mounted on a chrome plated brass eyewash assembly. Unit has a ANSI compliant sign.

DECK-MOUNTED EYE WASH (MODEL: G-1822)

Deck mounted eye wash with stainless steel bowl, 1/2" U.S. made chrome plated brass stay open ball valve, powder coated cast aluminum flag handle, and 1 1/4" mounting shank. Unit includes (2) polypropylene 'GS Plus' spray heads with integral "flip-top" dust covers, filters and 1.8-GPM flow control orifices mounted on a chrome plated brass eyewash assembly. Unit has a ANSI compliant sign.

WALL-MOUNTED EYE WASH (MODEL: G-1814)

Wall mounted eye wash with stainless steel bowl, 1/2" U.S. made chrome plated brass stay open ball valve, powder coated cast aluminum flag handle and wall bracket. Unit includes (2) polypropylene 'GS Plus' spray heads with integral "flip-top" dust covers, filters and 1.8-GPM flow control orifices mounted on a chrome plated brass eyewash assembly. Unit has a ANSI compliant sign.



Guardian



PRODUCT
DESCRIPTION

Safety Showers

BARRIER-FREE SAFETY STATIONS

(MODEL GBF1909 Barrier-Free Safety Station with WideArea™ Eye/Face Wash, Plastic Shower Head
(MODEL GBF1909SSH Barrier-Free Safety Station with WideArea™ Eye/Face Wash, Stainless Steel Shower Head)

Application: Barrier-Free combination WideArea™ eye/face wash and shower safety station. Shower head and pull rod are extended for improved access. Bowl is lowered and extended to permit access by wheelchair user. Profile of unit is "flattened" to comply with maximum height and knee clearance requirements.

ADA Compliance: Unit complies with ADA requirements for accessibility by handicapped persons (maximum height and reach, minimum knee clearance and distance from obstructions).

Shower Head: 10" diameter. Shower head is orange ABS plastic (GBF1909) or stainless steel (GBF1909SSH).

Shower Valve: 1" IPS chrome plated brass stay-open ball valve with stainless steel actuating arm and 47-1/2" stainless steel pull rod.

Spray Head Assembly: Four GS-Plus spray heads. Each head has a "flip-top" dust cover, internal flow control and filter to remove impurities from water flow.

Eye/face Wash Bowl: 11-1/2" stainless steel.

Eye/face Wash Valve: 1/2" IPS chrome plated brass stay-open ball valve with flag handle.

Pipe and Fittings: Schedule 40 galvanized steel. Furnished with orange polyethylene covers on piping for high visibility and corrosion resistance.

Supply: 1-1/4" NPT female top and side inlet.

Waste: 1-1/4" NPT female outlet. Outlet can be positioned at either 8" or 20" above finished floor by reversing lower pipe nipples.

Sign: ANSI-compliant identification sign.

Quality Assurance: Valve and spray head assemblies are factory assembled and water tested prior to shipment.



SAFETY SHOWERS

Available Options

- GC Powder coated finish on galvanized pipe and fittings. Available colors include orange, yellow, red and green
- BC Stainless steel cover for eye/face wash bowl
- FC20 Regulates shower flow rate to 20 GPM HS Auxiliary drench hose unit for rinsing eyes, face or body
- APBF250-015 Modesty Curtain Modesty curtain for mounting on Barrier-Free safety station
- AP275-200 Electric Light and Alarm Horn Flashing light and alarm horn for mounting on safety station
- TMV G3800 thermostatic mixing valve precisely blends hot and cold water to deliver warm

